

ALKYD INTERIOR VARNISH

CODE:	AIV
DESCRIPTION:	A general purpose varnish used on all interior wooden surfaces where a high gloss durable finish is required.
PRODUCT BENEFITS:	Compares favourably with conventional varnishes with regard to interior durability. Gives a good full gloss with a high degree of acceptance.
SURFACE PREPARATION:	NEW: Surface must be clean, dry and well sanded. Thin first coat 15 - 20% with mineral turps. Second and third coats should be applied undiluted. PREVIOUSLY VARNISHED: Surfaces in sound condition should be well sanded. Surfaces which are flaking and cracked must be stripped back to bare wood and proceed as for new wood.
PRECAUTIONS:	Not recommended for exterior use as it does not contain ultra violet light absorbers. Do not apply to wet/damp timber. It is important to varnish the end grain.
APPLICATION:	Ready for use by brush. Thin up to 20% with mineral turps for spray application. Clean up with mineral turps.
TECHNICAL DATA:	Type: Alkyd based SG: 0.85 - 0.92 Drying Time: (T) 4 Hours @ 25°C (H): 24 Hours Recoat: 16 Hours (overnight) Viscosity: 90 - 100 seconds Ford Cup 4 @ 25°C Spread Rate: Approx. 12m ² /L depending on surface profile and porosity. Flashpoint: 37°C Solids Volume: 40 - 44% Solids Mass: 52 - 55% Finish: High Gloss Colour Range: Clear transparent high gloss Pack Size: 500ml, 1L & 5L
Health and Safety:	Refer to Material Safety Data Sheet