



# BATHROOM & KITCHEN MATT

<b>CODE:</b>	<b>BAK</b>
<b>DESCRIPTION:</b>	A durable, highly washable interior, pure acrylic wall coating, using Silver Technology that protects the paint surface and inhibits the growth of micro-organisms. Suitable for direct application to new and previously painted plaster, composition board, fibre cement, wood and metal surfaces that have been correctly prepared, primed and undercoated. Useful alternative to solvent based eggshell or matt enamels where a low odour and quick dry matt finish is required.
<b>PRODUCT BENEFITS:</b>	Easily applied by brush, roller or airless spray. Quick drying. Low odour. Equipment easily cleaned in water. Non-yellowing. Outstanding durability and stain resistance.
<b>SURFACE PREPARATION:</b>	Surface to be painted must be thoroughly clean, dry and free from all foreign contaminants. Loose, flaking paint and efflorescence must be completely removed. All bare exposed metal surfaces must be spot primed with the appropriate primer and undercoat. Gloss and oil paint surfaces to be thoroughly sanded and wiped down with a damp cloth. Chalky surfaces must be thoroughly sanded before applying 1 coat Dekade Surface Conditioner diluted 20% with Mineral Turpentine. Kitchen walls without exception to be washed down with sugar soap.
<b>PRECAUTIONS:</b>	Do not paint in cold and wet weather. Do not apply to unprimed metal surfaces.
<b>APPLICATION:</b>	Stir thoroughly with flat paddle before use. Ready for use by brush, roller and airless spray. Thinning not normally necessary (use clean water if required). Clean up with water.
<b>TECHNICAL DATA:</b>	
Type:	Pure Acrylic.
SG:	1.26 - 1.28
Drying Time: (T) @ 25°C (H):	1 hour 4 hours
Recoat:	2 hours
Finish:	Matt
Viscosity:	100 - 105 KU
Solids Volume:	33 - 36%
Solids Mass:	44 - 46%
Spread Rate:	Approx. 10m <sup>2</sup> /Lt depending on surface profile and porosity.
Flashpoint:	Non-flammable
Colour Range:	White and Pastel Base
Pack Size:	1L & 5L

Health and Safety: Refer to Material Safety Data Sheet