

CHASSIS BLACK

CODE:

TCB

DESCRIPTION:

A high solids bitumen paint that is ideal for coating of chassis and under carriages of vehicles and trailers. For direct application to any clean surface where a low cost protective coating is required. May be used for sealing absorbent surfaces such as fibre cement.

PRODUCT BENEFITS:

Impervious to moisture and chemicals. Low cost. Acceptable sheen finish.

SURFACE PREPARATION:

No elaborate surface preparation necessary. Surface must be clean and dry. Apply 2 coats for new work, depending on severity of conditions. Do not overwork the brush on recoating as the coating is easily re-dissolved. For general maintenance or to seal absorbent surfaces, apply 1 coat.

PRECAUTIONS:

Do not expose to direct sunlight. Top coating with decorative coatings will result in "bleeding" of the bitumen. Not resistant to solvents.

APPLICATION:

Stir well with flat paddle before use. Ready for use with brush or roller. For spray application only - thin with Mineral Turpentine. Clean up with Mineral Turpentine or Trade Degreaser.

TECHNICAL DATA:

Type:	Bitumen
SG:	0.89 - 0.92
Drying Time: (T)	2 - 4 Hours
@ 25°C (H):	6 - 8 Hours
Recoat:	8 Hours
Viscosity:	80 - 85 KU
Solids by Volume:	68 - 72%
Solids by Mass:	72 - 74%
Spread Rate:	Approx. 10m ² /L depending on surface porosity
Gloss Level:	Sheen
Flashpoint:	37°C
Pack Size:	1L & 5L
Colour:	Black

Health and Safety:

Refer to Material Safety Data Sheet