

# POLYURETHANE VARNISH

**CODE:****WDV****DESCRIPTION:**

A single pack polyurethane varnish suitable for a wide range of interior wooden surfaces such as furniture, cupboards, T & G boards, skirting, doors and floors etc.

**PRODUCT BENEFITS:**

Provides a tough durable, mar resistant, professional finish. The extremely hard finish is resistant to heat from hot coffee cups, moisture, alcohol and other household stains. Very easy to apply with good flow characteristics. Choice of gloss or suede finish.

**SURFACE PREPARATION:**  
**New Work:**

Ensure surface is dry and free from oil, grease, grime, dust or any other surface contamination. Sand wood to a smooth surface, working with the grain. Test smoothness with fingertips. Dust or wipe clean with a "tack rag"

**Previously Painted:**

Surfaces in sound condition must be wiped down with Dekade Brush and Rinse Degreaser to remove wax or silicone polish. Finally wipe down or rinse surface with clean warm water. Sand lightly with 320 grit paper and wipe clean with "tack rag". Surfaces which are cracked or flaking must be completely stripped back to bare wood and proceed as for new timber.

**PRECAUTIONS:**

Not recommended for exterior use. Do not apply to wet or damp timber. Stir Suede version thoroughly before use. Do not paint in cold or wet weather.

**APPLICATION:**

Suede version must be well stirred before use. Ready for use by brush. Thin and clean up with Mineral Turpentine.

**TECHNICAL DATA:**

Type:	Single pack polyurethane
SG:	0.88 - 0.92
Drying Time: (T)	2 Hours
@ 25°C (H):	24 Hours
Recoat:	12 Hours
Viscosity:	35 - 45 seconds Ford Cup 4 @ 25°C
Spread Rate:	Approx. 12m <sup>2</sup> /L depending on surface porosity.
Flashpoint:	37°C
Solids Volume:	40 - 45%
Solids Mass:	44 - 50%
Finish:	High Gloss or Suede
Colour Range:	Transparent Clear Gloss or Suede Finish
Pack Size:	500ml, 1L & 5L

**Health and Safety:**

Refer to Material Safety Data Sheet