

SUPER BRIGHT ALUMINIUM

CODE:

TSA

DESCRIPTION:

Trade Super Bright Aluminium is a general purpose high lustre aluminium paint. Used for all interior/exterior primed metal and wooden surfaces where an aluminium finish is required. Excellent as a roof paint where its ability to reflect heat reduces the temperature inside the building.

PRODUCT BENEFITS:

Excellent durability. Reflects heat.
Improves illumination - good reflector of light.

SURFACE PREPARATION:

Surfaces must be clean, dry and free from any surface contamination. **GALVANISED IRON:** Fabricator's pre-treatment must be completely removed with Galvanised Iron Cleaner. Prime with WB Galvanised Iron Primer before applying Super Bright Aluminium. **ALUMINIUM:** Degrease then prime with Trade Etch Primer. **FERROUS METALS:** Loose surface rust must be removed by wire brushing. Mill scale must be removed by abrasive blast. Prime with Zinc Phosphate Primer then Trade Undercoat. **CEMENT:** Prime with Trade Plaster Primer then Trade Undercoat. **WOOD:** Prime with Trade Pink Wood Primer then Trade Undercoat. **FIBRE CEMENT:** Apply 1 coat Trade Bituminous Aluminium.

PRECAUTIONS:

Do not paint in cold and wet conditions. Do not apply to unprimed metal surfaces. Not suitable for surfaces which exceed 100°C.

APPLICATION:

Stir thoroughly with flat paddle before use. Ready for use with brush or roller. For spray application, thin with mineral turps. Clean up with Mineral Turps.

TECHNICAL DATA:

Type:	Oleoresinous
SG:	0.93 - 0.96
Drying Time: (T) @ 25°C (H):	4 Hours 16 Hours
Recoat:	16 Hours
Viscosity:	30 - 40 seconds Ford Cup 4
Spread Rate:	Approx. 18m ² /L depending on surface profile & porosity.
Flashpoint:	37°C
Solids Volume:	30 - 35%
Solids Mass:	50 - 55%
Recommended DFT:	15 - 20 micron
Finish:	Sheen
Colour Range:	Aluminium
Pack Size:	500ml, 1L, 5L, 20L

Health and Safety:

Refer to Material Safety Data Sheet