



TRADE RANGE

TECHNICAL
DATA SHEET

NACTM
NATAL
ASSOCIATED
CHEMICALS

FILLERCOAT

CODE:

TFC

DESCRIPTION:

Dekade Trade Fillercoat is an interior fillercoat for wood floated plaster where filling is required before top coating with various water based finishing coats, e.g. Trade Super Matt. Can also be used as a low cost finishing coat for interior use.

PRODUCT BENEFITS:

A high solids Acrylic Fillercoat. Good filling properties. Easy application with brush or roller. Quick drying.

SURFACE PREPARATION:

Surface to be painted must be thoroughly clean, dry and free from all foreign contaminants. All bare metal areas e.g. nail heads, must be primed with the appropriate primer. For rough concrete apply one or two coats depending on the degree of filling required. Best for interior use only.

GENERAL:

Do not apply to unprimed metal and wooden surfaces. Not recommended for exterior use.

APPLICATION:

Stir thoroughly with flat paddle before use. Ready for use by brush, roller or airless spray. Thinning not normally necessary as thinning will reduce opacity and filling properties. Clean up with water.

TECHNICAL DATA:

Type:	Acrylic PVA Copolymer
Drying Time: (T)	1 Hour
@ 25°C (H):	4 Hours
Recoat:	2 Hours
Viscosity:	100 - 105 KU
SG:	1.44 - 1.46
Solids by Volume:	29 - 32%
Spread rate:	At 75 microns dry film thickness, approx. 5m ² /L
Solids by Mass:	48 - 52%
Flashpoint:	Non flammable
Colour Range:	White
Pack Sizes:	5lt & 20lt
Finish:	Matt

Health and Safety:

Refer to Material Safety Data Sheet